

REVISIONS This drawing, specifications, and concepts contained here in are the sole property of DATE INITIAL APPROVED DESCRIPTION Red Barn Machine, and may not be reproduced or used in any fashion without the A CH'D -3 ENGRAVE NOTES PER R.W. 5/6/11 RJC prior written permission of Red Barn Machine. - 2.326 -- .388 2X .10 --Ø4.568 Ø4.221 -**ENGRAVE T/N** 2X 15° "RBW6305G15731-3G", Ø3.936 -S/N, "MADE IN USA" **ENGRAVE T/N** "RBW6305G15731-3G-3" Ø2.757 -B⊸ .12 X 45° <del>--</del> .630⊦ **SECTION B-B** ® RED BARN MACHINE TITLE TOOL, T/R DRIVE QUILL LIP SEAL INSTALLER DRAWN BY: CLDUGH DIMENSIONS ARE IN INCHES
TOLERANCES ON:
DECIMALS

METRIC REF. APPROVED D Weil METRIC REF. .XXmm ± .1mm .XXX ± .005 .XX ± .01 .X ± .1 FRACTIONS ± 1/32 CLEAR ANDDIZE ANGLES ±.5° <sup>SPEC</sup> MIL-A-8625F, TYPE II, CLASS I UNLESS OTHERWISE SPECIFIED 1. BREAK ALL SHARP EDGES

**BASE** 

USED ON MODEL

AW139

sheet 2 of 2

.015 x 45° PR .015 R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING

DATE

1:2

SCALE